



[electric sport bicycle](#)

Product Model: JB-TDE01Z Electric system Main components Motor Light weight high speed Frame 6061 Al alloy brushless hub motor Tyres 26"x1.95, KENDA brand 180W-250W for European Rim Al alloy double wall 250W-500W for USA & Canada Front fork Al alloy suspension, ZOOM 200W for Australia & N.Z. Front brake Disc brake Battery 36V/10Ah Lithium battery, Rear brake "V" brake (Disc brake available) with electric protection circuit Speed gears SHIMANO 6 speed gears Derailleur SHIMANO PAS 1:1 intelligent pedal assistant system Handle bar Al alloy With torque sensor controller. Stem Al alloy Controller 36V intelligent PAS, brushless Brake lever Al alloy, cut-off when braking Charger 100V-240V, 2 amps smart charger Chain Rust resistant chain Charge time: 4-6 hours Chain wheel Al alloy Throttle Twist intelligent speed control Mudguard PP plastic / Al alloy Performance Rear rack Al alloy Max. speed 25km/h (EU), 20mph (USA & Canada) Saddle Soft Comfortable Range 65KMS with pure electric Seat post Al alloy suspension 100KMS with PAS Pedal Al alloy MTB style with reflector Max load 100KGS Options Front/rear light, tool kit, rear rack Weight N.W: 24KGS, G.W: 27KGS Lock, Speed meter, helmet Dimension 148*28*78cm Capacity 108pcs/20ft, 216/40HQ container



electric sport bike

Product Model: JB-TDE01Z Electric system Main components Motor Light weight high speed Frame 6061 Al alloy brushless hub motor Tyres 26"x1.95, KENDA brand 180W-250W for European Rim Al alloy double wall 250W-500W for USA & Canada Front fork Al alloy suspension, ZOOM 200W for Australia & N.Z. Front brake Disc brake Battery 36V/10Ah Lithium battery, Rear brake "V" brake(Disc brake available) with electric protection circuit Speed gears SHIMANO 6 speed gears Derailleur SHIMANO PAS 1:1 intelligent pedal assistant system Handle bar Al alloy With torque sensor controller. Stem Al alloy Controller 36V intelligent PAS, brushless Brake lever Al alloy, cut-off when braking Charger 100V-240V, 2 amps smart charger Chain Rust resistant chain Charge time: 4-6 hours Chain wheel Al alloy Throttle Twist intelligent speed control Mudguard PP plastic / Al alloy Performance Rear rack Al alloy Max. speed 25km/h(EU), 20mph(USA&Canada) Saddle Soft Comfortable Range 65KMS with pure electric Seat post Al alloy suspension 100KMS with PAS Pedal Al alloy MTB style with reflector Max load 100KGS Options Front/rear light, tool kit, rear rack Weight N.W: 24KGS, G.W: 27KGS Lock, Speed meter, helmet Dimension 148*28*78cm Capacity 108pcs/20ft, 216/40HQ container



[mountain electric bike](#)

Product Model: JB-TDE01Z-2 Electric system Main components Motor Light weight high speed Frame 6061 Al alloy brushless hub motor Tyres 26"x1.95, KENDA brand 180W-250W for European Rim Al alloy double wall 250W-500W for USA & Canada Front fork Al alloy suspension, ZOOM 200W for Australia & N.Z. Front brake Disc brake Battery 36V/10Ah Lithium battery, Rear brake "V" brake(Disc brake available) with electric protection circuit Speed gears SHIMANO 6 speed gears Derailleur SHIMANO PAS 1:1 intelligent pedal assistant system Handle bar Al alloy With torque sensor controller. Stem Al alloy Controller 36V intelligent PAS, brushless Brake lever Al alloy, cut-off when braking Charger 100V-240V, 2 amps smart charger Chain Rust resistant chain Charge time: 4-6 hours Chain wheel Al alloy Throttle Twist intelligent speed control Mudguard PP plastic / Al alloy Performance Rear rack Al alloy Max. speed 25km/h(EU), 20mph(USA&Canada) Saddle Soft Comfortable Range 65KMS with pure electric Seat post Al alloy suspension 100KMS with PAS Pedal Al alloy MTB style with reflector Max load 100KGS Options Front/rear light, tool kit, rear rack Weight N.W: 24KGS, G.W: 27KGS Lock, Speed meter, helmet Dimension 148*28*78cm Capacity 108pcs/20ft, 216/40HQ container



[electric mountain bike](#)

Product Model: JB-TDE01Z-2 Electric system Main components Motor Light weight high speed Frame 6061 Al alloy brushless hub motor Tyres 26"x1.95, KENDA brand 180W-250W for European Rim Al alloy double wall 250W-500W for USA & Canada Front fork Al alloy suspension, ZOOM 200W for Australia & N.Z. Front brake Disc brake Battery 36V/10Ah Lithium battery, Rear brake "V" brake(Disc brake available) with electric protection circuit Speed gears SHIMANO 6 speed gears Derailleur SHIMANO PAS 1:1 intelligent pedal assistant system Handle bar Al alloy With torque sensor controller. Stem Al alloy Controller 36V intelligent PAS, brushless Brake lever Al alloy, cut-off when braking Charger 100V-240V, 2 amps smart charger Chain Rust resistant chain Charge time: 4-6 hours Chain wheel Al alloy Throttle Twist intelligent speed control Mudguard PP plastic / Al alloy Performance Rear rack Al alloy Max. speed 25km/h(EU), 20mph(USA&Canada) Saddle Soft Comfortable Range 65KMS with pure electric Seat post Al alloy suspension 100KMS with PAS Pedal Al alloy MTB style with reflector Max load 100KGS Options Front/rear light, tool kit, rear rack Weight N.W: 24KGS, G.W: 27KGS Lock, Speed meter, helmet Dimension 148*28*78cm Capacity 108pcs/20ft, 216/40HQ container



[light electric mountain bicycle](#)

Product Model: JB-TDE02Z Electric system Main components Motor Light weight high speed Frame 6061 Al alloy brushless hub motor Tyres 26"x1.95, KENDA brand 180W-250W for European Rim Al alloy double wall 250W-500W for USA & Canada Front fork Al alloy suspension, ZOOM 200W for Australia & N.Z. Front brake Disc brake Battery 36V/10Ah Lithium battery, Rear brake "V" brake(Disc brake available) with electric protection circuit Speed gears SHIMANO 6 speed gears Derailleur SHIMANO PAS 1:1 intelligent pedal assistant system Handle bar Al alloy With torque sensor controller. Stem Al alloy Controller 36V

intelligent PAS, brushless Brake lever Al alloy, cut-off when braking Charger 100V-240V, 2 amps smart charger Chain Rust resistant chain Charge time: 4-6 hours Chain wheel Al alloy Throttle Twist intelligent speed control Mudguard PP plastic / Al alloy Performance Rear rack Al alloy Max. speed 25km/h(EU), 20mph(USA&Canada) Saddle Soft Comfortable Range 65KMS with pure electric Seat post Al alloy suspension 100KMS with PAS Pedal Al alloy MTB style with reflector Max load 100KGS Options Front/rear light, tool kit, rear rack Weight N.W: 24KGS, G.W: 27KGS Lock, Speed meter, helmet Dimension 148*28*78cm Capacity 108pcs/20ft, 216/40HQ container

[mountain e-bike](#)

Product Model: JB-TDE03Z Electric system Main components Motor Light weight high speed Frame 6061 Al alloy brushless hub motor Tyres 26"x1.95, KENDA brand 180W-250W for European Rim Al alloy double wall 250W-500W for USA & Canada Front fork Al alloy suspension, ZOOM 200W for Australia & N.Z. Front brake Disc brake Battery 36V/10Ah Lithium battery, Rear brake "V" brake (Disc brake available) with electric protection circuit Speed gears SHIMANO 6 speed gears Derailleur SHIMANO PAS 1:1 intelligent pedal assistant system Handle bar Al alloy With torque sensor controller. Stem Al alloy Controller 36V intelligent PAS, brushless Brake lever Al alloy, cut-off when braking Charger 100V-240V, 2 amps smart charger Chain Rust resistant chain Charge time: 4-6 hours Chain wheel Al alloy Throttle Twist intelligent speed control Mudguard PP plastic / Al alloy Performance Rear rack Al alloy Max. speed 25km/h(EU), 20mph(USA&Canada) Saddle Soft Comfortable Range 65KMS with pure electric Seat post Al alloy suspension 100KMS with PAS Pedal Al alloy MTB style with reflector Max load 100KGS Options Front/rear light, tool kit, rear rack Weight N.W: 24KGS, G.W: 27KGS Lock, Speed meter, helmet Dimension 148*28*78cm Capacity 108pcs/20ft,



216/40HQ container

[Electric bikes](#), [electric bike](#), [electric bicycle](#), [electric bicycles](#), [electric mountain bikes](#), [mountain electric bikes](#), [city electric bikes](#), [ladies electric bike](#), [folding electric bike](#), [folding electric bikes](#), [hot electric motor bikes](#), [latest electric motor bikes](#), [heavy duty e-bike](#), [US standard electric bikes](#), [EU standard electric bikes](#), [Electric bicycles Size](#), [16 electric hybrid bicycle](#), [16" PAS electric hybrid bicycle](#), [16" GAS electric hybrid bicycle](#), [20 electric hybrid bicycle](#), [20" PAS electric hybrid bicycle](#), [20" GAS electric hybrid bicycle](#), [24 electric hybrid bicycle](#), [24" PAS electric hybrid bicycle](#), [24" GAS electric hybrid bicycle](#), [26 electric hybrid bicycle](#), [26" PAS electric hybrid bicycle](#), [26" GAS electric hybrid bicycle](#), [Electric bicycles](#), [cheap electric power bikes](#), [steel frame electric motor bikes](#), [lead acid battery powered bikes](#), [high quality electric bicycles](#), [aluminum alloy LEV](#), [lithium Battery powered bikes](#), [Electric bike fittings](#), [Electric bike parts](#), [e-bike conversion kit](#), [electric assist bikes](#), [e-bike accessories](#), [optional e-bike fittings](#), [Electric scooter bikes](#), [36 Volt series](#), [48 Volt series](#), [Electric tricycle](#), [electric Pedicabs](#), [leisure series](#), [freight series](#), [Electric motorbikes](#),

JIABAO E-Vehicle Co., Ltd.

Add: No. 1868 Jinqiu Road, Wucheng, Jinhua City, Zhejiang Province, China

Contact: Miss Ivy Wang

Tel: 579-83236566

Fax: 579-83236569

E-mail: sales@jb-electricbikes.com

Website: <http://www.jb-electricbikes.com>